KFP-AF1-09

KILSEN Addressable Fire Panel - 1 Loop - Spanish

Overview

The KFP-A Series life safety control systems are bringing the speed and functionality of high-end intelligent processing to small to mid-sized addressable applications. They feature an attractive contemporary design that fits with any decor. Special plastics allows for painting in any color and the easy to remove electronics will support in this matter. The gently curved door with the intuitive dark inset user interface and EN54 compliant graphical LCD offers a distinctive flair. The main controls are clearly, but discreetly highlighted with the focus on the central located Jog Dial.

With the addressable detection and a full line of easily configured option cards and modules, USB and Ethernet® connectivity, these quick-to-configure systems offer versatility that benefits building owners and life safety system installers alike.

The Panel

The fire panels supplied in local language, with user interface, with 1 loop that supports up to 250 devices in 512 zones, have standard 2 supervised sounder/fire-routing outputs, which can be used as freely programmable outputs as well. In addition 2 conventional relay outputs and 2 supervised outputs, working in pair and dedicated to common fire and fault conditions, as well as 2 user configurable inputs for monitoring and control are available.

Options

The panels supports one network board to create a maximum of 32 nodes / 32 loops network of fire panels, fire panel repeaters (including conventional fire panels and fire panel repeaters up to a maximum of 64 conventional zones). Last but not least, in case seperate zone indications are required, a 20 or 40 zone fire/fault LED indicator board can be mounted in the panel or repeater with ample space for text.

Approvals & Compliance

- CE / CPD / EN54-2 / EN54-4
- NEN2535 / NBNS21-100 compliant
- BS5839-1 compliant
- VdS and LPCB certified
- WEEE / RoHS compliant



Details

- 1 loop with up to 512 zones
- Up to 40 LED Zone indicators for Fire and Fault with ample text space
- Auto configuration and default regional setup modes
- Ethernet port with TCP/IP for remote maintenance and programming
- EN54 compliant graphical LCD with icons and up to 256 zones
- Jog Dail with 4 soft buttons for simple and intuitive user control
- Aesthetic pleasing design with special paintable synthetic door
- Easy removable door and chassis for quick and clean installation
- All pluggable connectors
- 3 USB ports with memory stick support
- 3 RS232 ports
- Auxiliary 24VDC supply output with reset support
- 3 operator level menu structure
- History log memory for 9999 events
- Up to 72 hours standby time and 30 minutes alarm
- Compatible with the KL700A series detectors with replaceable optical chamber and loop powered sounders and base sounders

KFP-AF1-09

KILSEN Addressable Fire Panel - 1 Loop - Spanish

Technical specifications

General

Maximum system capacity (device count)	up to 16000
Network size (nodes)	up to 64

Electrical

Power supply type	VAC
Operating voltage	110/230 VAC (+10%/-15%), 50 / 60 Hz (±5%) Cable type: 3 x 1.5 mm² (live, neutral, earth)
Current consumption	Nom. 0.6 / 1.3 A, Max. 1.5 / 3.15 A

Loop

Maximum loop capacity	1
Cable rating	Recommended 2 core 1.5 mm² twisted pair, 56 ohm, 1 µF, max. 4 km

Zone

Maximum zone capacity	up to 512

Input

Input type and rating	150 mA (max. Load), Cable type: Recommended 2 core 1.5 mm² twisted pair
Programmable	2
Termination	15 kohm

Output

Output type and rating	Cable type: Recommended 2 core 1.5 mm² twisted pair
Termination	15 kohm

Standby battery

Capacity	Max. 2 x 12 V, 18 Ah (use supplied cables)

Physical

Form factor	Stor
Physical dimensions	450 x 581 x 169 mm (W x H x D)
Net weight	7.4 kg (without battery)
Shipping weight	10.1 kg
Colour	Ren hvid (RAL 9010)
Mounting type	Overflademontering
Cable entries	18 (20 mm) / 2 (20 mm) / 2 removable plates (Top /Bottom/Back)

Environmental

Operating temperature	-8 to +42°C
Storage temperature	-10 to +50°C
Relative humidity	95% max. noncondensing
Environment	Indendør
IP rating	IP30: for indoor use only

Regulatory

Compliancy	BS5839-1, CPD, LPCB, NBNS21-100, NEN2535, RoHS, WEEE
Certification	EN54-13, EN54-2, EN54-21, EN54-4, VdS

Mains supply

Fuse rating	2 / 4 A

Outputs

Programmable supervised	2, 750mA / 19.5-28VDC (24VDC nominal)
General Fire + Fault supervised	2, 350mA / 19.5-28VDC (24 VDC nominal)
General Fire + Fault relay	2
Aux	1 resetable, 500mA / 19.5-28VDC (24VDC nominal)

Loops

Outputs	1, 250 mA / 29VDC (29VDC to 36VDC)

Mechanical


Size (W x D x H)	449.6 x 169.4 x 580.8 mm
Weight	7.4 kg (without batteries)
Color	RAL9010
Cable entries (Top / Bottom / Back)	18 (20mm) / 2 (20mm) / 2 removable plates
IP rating	IP30: for indoor use only

Compatible products

Category	Reference	Description
Batteries	BS131N	Battery, 12 V, 18 Ah
Panel	2010-2-NB	Addressable fire panel accessory, network printed circuit board
Panel	2010-2-PAK-NET128	2010-2 PAK increases the network capability to 32 nodes and 128 loops
Panel	2010-2-PAK-RMMB	2010-2 PAK Enables the Modbus protocol over Ethernet
Panel	2010-2-PAK-RMOH	2010-2 PAK enables Contact ID protocol over Ethernet
Panel	2010-2-PAK-RMSDK	2010-2 PAK enables custom event reporting and command control using the Edwards

KFP-AF1-09

KILSEN Addressable Fire Panel - 1 Loop - Spanish



KIDDE COMMERCIAL

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 6 October 2026 - 9:04