# DDV1016AM-D-B-N

## 16 m, Dual, 9 Vorhänge, AM, VdS/EN Grad III, dunkelgrau, digitale Pyro, neuronaler Algorithmus, VdS G122030

### Patented Range Gated Radar Technology

Motion sensors of the DDV1016 Series incorporate a patented and unique range gated radar technology allowing the installer to define a clear borderline of the radar range as the radar is used to measure distance between the sensor and moving objects. Effectively the end-user will get rid of any nuisance alarms generated by movements outside the detection pattern.
Every motion sensor comes with 4 possible radar ranges selectable via dip switches allowing the detection pattern to be tailored according to the room where the motion sensor is installed.
The radar operates on 5.8 GHz frequency.

### PIR Technology in combination with patented mirror optics

Our patented optical mirror technology gives the advantage of gliding focus, which creates a continuous detection curtain from floor level up to installation height.
Within our DDV1016 series we are using a dual element pyro generating 2 volumetric curtains for each of the 9 curtain sets.

### Detection technologies working together

These dual tech motion sensors generate an alarm depending on what both technologies – range gated radar and PIR – saw within its detection coverage.
But our dual tech go beyond a simple “AND” function : it classifies the signals from each technology – range gated radar and PIR – to have the best alarm result without being sensitive for nuisance signal sources. This technology creates a uniform sensitivity in all course directions.

### Ease and flexibility of installation

1. Tolerates wall angle deviation and different mounting heights.
2. Limited loss of coverage when objects are placed in the field of the PIR vision.
3. Easy range setting via dip switches of the range gated radar in order to tailor the detection pattern to your needs.
4. Multiple build-in End-Of-Line resistor values with “easy wiring” option available.
5. Plug-in connector.

### Anti-masking (optical and radar)

The use of Active Infrared and radar technology results in a superior anti-masking functionality that supervises the motion sensor on the inside and outside. Radar verification prevents from having unwanted AM alarms caused by e.g. insects. In advanced setting the AM alarm is held until the effective source of the anti-masking (e.g. spray, tape,…) has been removed. Even partial masking - so going beyond the EN Grade III standard - will be detected when in advanced setting.

### Other members of the family



### Einzelheiten

- Patentierte, wählbare Range-Gated-Radar-Technologie, die die Radarerfassungsgrenze klar definiert
- PIR-Technologie mit patentierter Spiegelvorhang-Optik
- Anti-Masking-Variante mit Aktiv-Infrarot- und Radartechnologie zum Schutz vor Sabotageakten außerhalb und innerhalb des Bewegungsmelders
- Intelligente Alarmentscheidung auf Basis der Signalklassifizierung des PIR- und Radar-Alarms
- Automatische kontinuierliche Selbstdiagnose bei allen Technologien
- Grüner Modus: Option zum Abschalten der Radartechnologie, wenn das Sicherheitssystem nicht scharf ist
- Verfügt über ein neues digitales Pyro, das die Temperaturschwankungen mit hoher Präzision erkennt
- Enthält einen brandneuen neuronalen Algorithmus, der unerwünschte Alarme herausfiltert

The consistent family aesthetics between the various models ensure a professional approach when installing different sensor types.

## Neural network-based technology algorithm

Aritech has developed an improved algorithm based on cutting edge neural network-based technology to improve the detection performance and reduce false alarms triggered by external sources. Neural networks are trained to extract complex image features effectively; it allows the detection of slow motion even further apart from the detector.
This algorithm has the aim to improve even further the immunity to false alarms, which is a key concern for major applications of sensors in commercial settings.

## Neural network-based technology algorithm

Aritech has developed an improved algorithm based on cutting edge neural network-based technology to improve the detection performance and reduce false alarms triggered by external sources. Neural networks are trained to extract complex image features effectively; it allows the detection of slow motion even further apart from the detector.
This algorithm has the aim to improve even further the immunity to false alarms, which is a key concern for major applications of sensors in commercial settings.

# DDV1016AM-D-B-N

## 16 m, Dual, 9 Vorhänge, AM, VdS/EN Grad III, dunkelgrau, digitale Pyro, neuronaler Algorithmus, VdS G122030

## Technische Spezifikationen

### General

| | |
|---|---|
| Technology | Dual |
| Application type | Wall mount |
| Anti masking | Yes |
| Pet immune | No |
| Camera | No |
| Pry-off tamper kit | On board |
| Detector start-up time | 60 s |

### Detection

| | |
|---|---|
| Max. detection range | 16 m |
| Detection range selection | 10, 12, 14 oder 16 m über Dip-Schalter wählbar |
| No. of curtains | 9 |
| Coverage (field of view) | 78° |
| Microwave frequency (nom.) | 5.8 GHz |
| Max. microwave output (at 1m) | 0.003 µW/cm² |
| Undercrawl protection | Yes |
| Target speed range | 0.1 bis 4.0 m/s |
| Alarm memory | Yes |
| Alarm time | 3 s |
| Peak-to-peak ripple immunity | 2 V (bei 12 VDC) |

### Wired/wireless

| | |
|---|---|
| Wired-wireless | Wired |

### Inputs/outputs

| | |
|---|---|
| Alarm relay characteristic | NC, 80 mA, 30 VDC, Form A |
| Tamper relay characteristic | NC, 80 mA, 30 VDC, Form A |
| Anti mask relay characteristic | NC, 80 mA, 30 VDC, Form A |
| Remote control lines | Day/Night, Walk test |

### Electrical

| | |
|---|---|
| Operating voltage | 9 bis 15 VDC |
| Current consumption | 10 bis 22 mA (11 mA nom.) |

### Physical


| | |
|---|---|
| Physical dimensions | 126 × 63 × 50 mm |
| Net weight | 120 g |
| Colour | Dark grey |
| Mounting height | 2 to 3 m |

### Environmental

| | |
|---|---|
| Operating temperature | -10 bis +55°C |
| Relative humidity | 95% max. nicht kondensierend |
| Environment | Indoor |
| IP rating | IP30 |

### Regulatory

| | |
|---|---|
| Certification | EN50131 Grade 3, VdS |
| Standards | VdS G122030 |




Als innovatives Unternehmen behält sich Kidde Global Solutions das Recht vor, Produktspezifikationen ohne Ankündigungen zu ändern. Für die aktuellsten Produktspezifikationen, besuchen Sie bitte de.firesecurityproducts.com online oder kontaktieren Sie bitte unsere Vertriebsmitarbeiter.