AS612

Self-activating outdoor siren with amber beacon - IMQ



Details

- Attractively shaped housings
- High-quality dual skinned design
- 120 dB @ 1 m sound output
- Lead acid battery back-up for up to 7.2 Ah
- Steel inner cover with foam resistant grid
- Fully potted electronics
- Pry-off and opening tamper detection
- Strobe flash light
- Self detection of cable cutting or tampering
- Automatic polarity selection
- Independent hold-off for both beacon and siren
- Choice of cut-off time

AS612

Self-activating outdoor siren with amber beacon - IMQ

Technical specifications

General

Accessory group	Siren
Type	Outdoor siren
Sounder output (dB @ distance)	120 dB at 1 m (typical)

Flash specifications

Current consumption	110 mA
Light output	100,000 peak lumens
Flash frequency	60 flashes/minute

Electrical

Operating voltage	13 to 14.2 V
Current consumption	600 mA 25 mA (standby current)

Physical

Physical dimensions	210 x 300 x 87 mm (W x H x D)
Net weight	2680 g
Material	Polycarbonate

Environmental

Operating temperature	-25 to 55 °C
IP rating	34

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 21 January 2026 - 19:51