# PM841

**Boxed switch mode, power supply, 12 VDC, 1 A**



## Details

- Continuous full rated current to load
- Additional 0.5 A to charge standby battery
- High efficiency electronics for reduced running costs and lower operating temperatures
- Modular construction for ease of maintenance and installation

# PM841

## Boxed switch mode, power supply, 12 VDC, 1 A

## Technische specificaties

### General

| | |
|---|---|
| Fuse(s) | 230 VAC input 2A, 12/24V output 1 A |

### Electrical

| | |
|---|---|
| Mains input | 100 to 240 VAC |

### Output

| | |
|---|---|
| Power output voltage | 13.8 VDC |
| Output ripple | 150 mV pk-pk max |
| Power output current mains | 1 A |

### Battery

| | |
|---|---|
| Max. Battery capacity | 7.2 Ah |
| Battery charge current | 0.5 A |

### Physical

| | |
|---|---|
| Colour | White |
| Form factor | Steel cabinet |

### Regulatory

| | |
|---|---|
| Compliancy | CE, REACH, RoHS 2, WEEE |

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57