DI601AM

Outdoor, PIR, Anti Mask, selectable 10/20/30 m



Details

- Electronic range setting: 10/20/30m
- 10 to 70º detection angle
- -45° to +45° pan and +45° tilt for flexible install
- Sensor module is hidden
- Built-in EOL resistors with triple EOL configuration capability
- High dust and humidity resistance (IP55)
- 5 years warranty

DI601AM

Outdoor, PIR, Anti Mask, selectable 10/20/30 m

Technische specificaties

General

Technology	PIR
Application type	Wall mount
Anti masking	Yes
Pet immune	No
Camera	No

Detection

Max. detection range	30 m
Detection range	30 m
Detection range selection	10, 20 or 30 m
Coverage (field of view)	70°
Undercrawl protection	No
Alarm time	5 s

Wired/wireless

Wired-wireless	Wired

Inputs/outputs

Alarm relay characteristic	NC / NO, Volt free relay, signal contact 24 VAC/DC at 50 mA with an integral 25 Ohm series resistor
Anti mask relay characteristic	Volt free relay, signal contact 24 VAC/DC at 50 mA with an integral 25 Ohm series resistor
Relay configuration	Multiple EOL values

Electrical

Power supply value	10 to 15 VDC
Current consumption	16 mA

Physical

Physical dimensions	125 × 175 × 130 mm
Net weight	348 g
Shipping weight	534 g
Colour	Silver
Material	High impact ABS plastic with HDPE cover, UV stabilized
Mounting height	3 to 6 m

Environmental

Operating temperature	-30 to +65°C
Environment	Outdoor
IP rating	IP55

Regulatory

EN50131 grade	Grade 3

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57