DMN700E-IS

ATEX-klassad larmknapp röd, 560 ohm, IP67. Bakstycke DMN787 och lock DMN78206 beställs separat.

Allmänt

DMN700E-IS är en egensäker larmknapp avsedd för tillämpningar i explosionsfarliga områden där en kapslingsklass upp till IP67 krävs. Den levereras med utbytbara anslutningar, som säkerställer enkel installation och underhåll. Montering av enheten görs också enkelt med en enkel snäpp passform och 4 skruvarna som håller fast enhetenThe DMN700E-IS is an Intrinsically safe MCP, designed for applications where an ingress protection rating up to IP67, is required. It comes with snap on connections, which ensure ease of installation and maintenance. Assembly of the unit is also made easy with a simple snap on fit, and 4 screws to secure the unit.



Installation

Installation time and ultimately cost, are of paramount importance. The MCP range directly reflects this need by providing a unique ‘plug and play’ concept designed specifically to reduce installation time. All new MCP products utilise a special terminal block, where all initial installation cabling is terminated. This terminal block is then simply connected to the back of the MCP. Simple,but effective, with no re-termination required and no time wasted.

Options and Approvals

Through new standards and legislation, both glass and re-settable operating elements may be used. To provide the greatest ‘flex-ability’, the new MCP range can be configured as either break glass or re-settable unit by simply changing from one element to another. No other additional parts or alternative products are required. Full compliance with the latest standards is essential and the new MCP outdoor call point range is approved to the latest EN54-11 standard

Detaljer

- Easy to install
- With break glass or resettable element
- Easy to replace glass
- High quality micro switch
- IP67 rated
- EN54-11 & CPD approved

DMN700E-IS

ATEX-klassad larmknapp röd, 560 ohm, IP67. Bakstycke DMN787 och lock DMN78206 beställs separat.

Tekniska specifikationer

Detection

Monitoring	Activated, Off

Physical

Colour	Red (RAL 3001)
Mounting type	Back box
Material (body)	PC / ABS

Environmental

Vandal proof	No
Environment	Indoor, IS, Outdoor

Regulatory

Compliancy	CE, REACH, RoHS 2, WEEE
Certification	CENELEC/ATEX, CPR

Kompatibla produkter

Kategori	Referens	Beskrivning
Detection device	DM715	DM715 Glas
Detection device	DMN782	Skyddslock till larmknapp DMN700 och DM2010. Passar även till DMN900 och KAL455-serien.

Kidde Global Solutions förbehåller sig rätten att ändra produktspecifikationer utan föregående meddelande. För de senaste produktspecifikationerna, besök se.firesecurityproducts.com online eller kontakta din försäljningsrepresentant.

Last updated on 12 November 2026 - 18:57