# DDI602-F2

**Detetor, Dupla Tecnologia, Exterior, 10/20/30 m, 10.585 GHz**



# DDI602-F2

## Detetor, Dupla Tecnologia, Exterior, 10/20/30 m, 10.585 GHz

## Especificações técnicas

### General

| | |
|---|---|
| Technology | Dual |
| Application type | Wandmontage |
| Anti masking | No |
| Pet immune | No |
| Camera | No |

### Detection

| | |
|---|---|
| Max. detection range | 30 m |
| Microwave frequency (nom.) | 10.587 GHz |
| Undercrawl protection | No |
| Alarm time | 5 sek |

### Wired/wireless

| | |
|---|---|
| Wired-wireless | Verdrahtet |

### Inputs/outputs

| | |
|---|---|
| Relay configuration | Mehrere EOL-Werte |

### Physical

| | |
|---|---|
| Colour | Silber |
| Material | Hochschlagfester ABS Kunststoff mit HDPE Abdeckung, UV stabilisiert |
| Mounting height | 3 bis 6 m |

### Environmental

| | |
|---|---|
| Environment | Draussen |

### Regulatory

| | |
|---|---|
| Certification | INCERT |

Como empresa de inovação, a Kidde Global Solutions reserva o direito de alterar as especificações do produto sem aviso prévio. Para obter informações sobre as especificações mais recentes do produto, visite pt.firesecurityproducts.com online ou contate o departamento comercial.

Last updated on 12 November 2026 - 18:57