# ACL585

## Vandal proof slim keypad, moulded aluminum, standalone

### Standalone vandal-proof keypad

Mullion and vandal-resistant access control keypad with metal keys for doorframe mounting. With user memory of 1000 codes and one push button, ACL585 is the best solution for single door access control. Photoelectric sensor for automatic illumination is effective in low-lit conditions. ACL585 with a rugged good look is designed to operate even in harsh environments.




### Details

- Indoor/outdoor
- Slim moulded aluminum housing with metal keys
- Dust proof and water-resistant
- Up to 1000 user codes
- Request To Exit using normal RTE button or ACL870 type pushbutton
- Codes can be 1 to 8 digit long
- 30 second lockout after eight consecutive invalid PINs

# ACL585

## Vandal proof slim keypad, moulded aluminum, standalone

## Technical specifications

### General

| | |
|---|---|
| User interface | Touch Buttons |
| Product line | Autonom |

### Communication

| | |
|---|---|
| Communication type | Kablede |

### Inputs/Outputs

| | |
|---|---|
| Inputs | 1 |
| Input type | Request-to-exit |
| Outputs | 1 |
| Output type | SPDT relay, latch or pulsed mode (01 to 99 seconds) |

### Electrical

| | |
|---|---|
| Operating voltage | 12 / 24 VAC/VDC |
| Current consumption | 70 mA max. |

### Physical

| | |
|---|---|
| Physical dimensions | 150 x 50 x 25 mm |
| Form factor | Lodret |
| Mounting type | Montaje en Superficie |
| Material | Støbt aluminium |

### Environmental

| | |
|---|---|
| Operating temperature | -25 to +50°C |
| Relative humidity | 95% noncondensing |
| IP rating | IP65 |

### Regulatory

| | |
|---|---|
| Compliancy | CE |
| Certification | CE |

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 18 June 2026 - 14:24