# SC-33-0230-0001-99

## Information White Sounder and Ceiling Visual Indicator (Blue Flash)

### Overview

The SmartCell Information Sounder and Visual Indicator is quick and easy to install and offers individual addressing at the SmartCell Control Panel.

Features include visual indicator (blue flash), 32 sounder tones, bidirectional 868 MHz communication and an anti-tamper locking mechanism.

This device is third party certified and compatible with the full SmartCell product range.



### Details

- Fully wireless
- Quick and easy to install
- Includes visual indicator (blue flash)
- Unique design
- Inbuilt locking mechanism
- NOT FOR FIRE OR SECURITY APPLICATIONS

# SC-33-0230-0001-99

## Information White Sounder and Ceiling Visual Indicator (Blue Flash)

## Technical specifications

### General

| | |
|---|---|
| Wireless frequency | 868 MHz |

### Electrical

| | |
|---|---|
| Batteries | 3 x 3.6 V lithium thionyl chloride batteries.<br>Fanso: ER14505M<br>HCB: ER14505M (HCB-JS-TZ-02-547) |

### Sounder

| | |
|---|---|
| Output level | 92 dB(A) at 1m max. |
| Output level adjustment | High or low |
| Selectable tones | 32 |

### VID

| | |
|---|---|
| Colour | Blue flash |
| Flash frequency | 0.5 Hz (1 flash, every 2 seconds) |

### Physical

| | |
|---|---|
| Physical dimensions | 110 x 94 mm (Ø x D) |
| Net weight | 0.2 kg |
| Colour | Hvid |

### Environmental

| | |
|---|---|
| Operating temperature | -10 to +55 °C |
| Storage temperature | -10 to +30 °C (with batteries)<br>-10 to +55 °C (without batteries) |
| Relative humidity | 0 to 95% noncondensing |
| Environment | Indendør |
| IP rating | IP21C |

### Regulatory

| | |
|---|---|
| Compliancy | CE |
| Certification | CPR |
| Standards | EN54-13 |

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 2 April 2026 - 13:15