FP2864C-32

2000 Series Addressable Fire Panel, 2 - 8 loops, 16 - 64 zones



Details

- One-man maintenance
- Maintenance warnings
- Soak test and service switces for diagnostics and maintenance
- On-line diagnostics and statistics
- Power supply for 72-hour autonomy
- Floating background for sensors
- Coincidence within and between zones
- Default start-up modes for quick configuration
- Upload/download, remote maintenance and graphic PC software
- I/O programming with Boolean functions
- Up to 8 class-A loops
- Up to 128 device addresses per loop (protocol dependant)
- Full range of LON700 devices
- Full interpanel network options
- Networkable "black box" and "global zoning"
- EN54 and CPD certified

FP2864C-32

2000 Series Addressable Fire Panel, 2 - 8 loops, 16 - 64 zones

Technische specificaties

General

Maximum system capacity (device count)	hasta 30K
Network size (nodes)	mere end 128

Loop

Maximum loop capacity	8

Zone

Maximum zone capacity	hasta 256

Physical

Form factor	Stor
Colour	Blanco (RAL 9016)
Mounting type	Montaje en Superficie

Regulatory

Certification	EN54-2, EN54-4

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57