KZD705

Kilsen KC700 / KA700 / KM300 series deep point detector base

General

The KZD705 is a 5 contact universal detector deep base for use with Kilsen KL700 and KL700A series detectors. In addition to the normal base and remote indication connectors, the KZD705 also has an additional earth terminal connector to allow for easy terminations of a possible cable screen. This deep base allows for rear cable entry as well as side cable entry with up to 25 mm conduit directly into the base.



Details

- Universal base fits conventional and addressable detectors
- Additional earth terminal available
- Remote indicator contact available
- Rear and side cable entry support
- Direct 25 mm conduit entry support for full surface mount applications

KZD705

Kilsen KC700 / KA700 / KM300 series deep point detector base

Technical specifications

Physical

Physical dimensions	124 x 40 mm (Ø x h)
Net weight	60 g
Mounting type	Loftmontering, Vægmontering

Environmental

Operating temperature	-10 to +70°C
Storage temperature	-10 to +70°C
Relative humidity	10 to 95% noncondensing
Environment	Indendør

Compatible products

Category	Reference	Description
Detection device	KL710	KILSEN KC700 Series conventional heat detector
Detection device	KL731	KILSEN KC700 Series conventional optical smoke detector
Detection device	KL731A	KILSEN KA700 Series addressable optical smoke detector
Detection device	KL735A	KILSEN KA700 Series addressable multisensor

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 6 October 2026 - 9:33