ACL580WI

Teclado standalone em alumínio moldado

Advanced keypads for access control and home automation

These standalone robust keypads are designed to operate in both indoor and outdoor environments. ACL580 keypads are available with backlit metallic/plastic keys and in a variety of plastic or metal housing options. These keypads offer elegant looks with a host of programmable options such as backlit keys, 1000 users, invalid code lockout, 2 pushbutton inputs, support for ACL870 push buttons, adjustable unlock timer etc. Can control two doors. Available in metal or plastic and surface or flush mounted.



Detalhes

- Indoor/outdoor
- Moulded aluminum housing with metal keys
- Dust proof and water-resistant (IP65)
- Up to 1000 user codes
- Request To Exit using normal RTE button or ACL870 type pushbutton
- Codes can be 1 to 8 digit long
- Users can be assigned any of the available relays
- 30 second lockout after eight consecutive invalid PINs
- Red and green LED (relay status) and orange LED (Programming)

ACL580WI

Teclado standalone em alumínio moldado

Especificações técnicas

General

User interface	Touch-Tasten
Product line	Autonome
Status LEDs	3

Communication

Communication type	Verdrahtet

Inputs/Outputs

Inputs	2
Input type	Request-To-Exit
Outputs	2
Output type	2 SPDT relays, Latch or pulsed mode (01 to 99 seconds)

Electrical

Operating voltage	12 / 24 VAC/VDC
Current consumption	150 mA max

Physical

Physical dimensions	120 x 90 x 40 mm
Form factor	Vertikal
Mounting type	Montage en surface
Material	Geformtes Aluminium

Environmental

Operating temperature	-20 to +50°C
Relative humidity	95% noncondensing
IP rating	IP65

Regulatory

Compliancy	CE
Certification	CE

Como empresa de inovação, a Kidde Global Solutions reserva o direito de alterar as especificações do produto sem aviso prévio. Para obter informações sobre as especificações mais recentes do produto, visite pt.firesecurityproducts.com online ou contate o departamento comercial.

Last updated on 12 November 2026 - 18:57