# DP721T

**Multi criteria optische rookmelder met thermo element op ± 60° C**



# DP721T

## Multi criteria optische rookmelder met thermo element op ± 60° C

## Technische specificaties

### Electrical

| | |
|---|---|
| Power supply type | Zone powered |

### Detection

| | |
|---|---|
| Monitoring | Alarm threshold, Contamination level |

### Physical

| | |
|---|---|
| Colour | Cloud white (RAL 9001) |
| Mounting type | Ceiling mount |
| Material (body) | Plastic |

### Environmental

| | |
|---|---|
| Vandal proof | No |
| Application temperature (typical) | +25°C |
| Environment | Indoor |

### Regulatory

| | |
|---|---|
| Compliancy | CE, REACH, RoHS 3, WEEE |
| Certification | CPR |

### Compatibele producten

| Categorie | Referentie | Beschrijving |
|---|---|---|
| Detection device | DB702 | Universele montagevoet voor 700 serie rookmelders met 6 aansluitklemmen |
| Notification device | AI672 | Nevenindicator uitgevoerd met 2 grote leds, 6-28VDC, 4 mA nominaal |
| Notification device | AI673 | Nevenindicator voorzien van akoestische signalering middels bleeper, 2 leds |

KIDDE GLOBAL SOLUTIONS

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar nl.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57