9-30441-JUM

Karta APIC adresowalnego interfejsu Excellence do Modulaser - Moduł rozszerzający

Description

The 9-30441-JUM is used in conjunction with the 9-30441 when more that five APIC's are required to be used on one addressable loop. With the 9-30441-JUM the amount of APIC's on the addressable loop can be increased up to a maximum of 10.

Fitment

The 9-30441-JUM plugs directly into the ModuLaser display module backplane, and in turn the addressable loop is wired directly to the 9-30441-JUM.

Szczegóły

- Prosta rozbudowa za pomocą wtyczki
- Rozszerzenie liczby układów APIC obsługiwanych w pętli adresowalnej
- Podłączenie do płyty modułu wyświetlacza ModuLaser

9-30441-JUM

Karta APIC adresowalnego interfejsu Excellence do Modulaser - Moduł rozszerzający

Specyfikacja techniczna

Environmental

Operating temperature	-20ºC do +60ºC
Relative humidity	10 do 95% bez kondensacji
Environment	Indoor

Wyroby zgodne

Kategoria	Odniesienie	Opis
Detection device	9-30441	Karta APIC adresowalnego interfejsu Excellence do Modulaser

Będąc firmą innowacyjną, Kidde Global Solutions zastrzega sobie prawo do zmian w specyfikacji wyrobów bez uprzedzenia. W celu uzyskania najnowszych specyfikacji prosimy o wizytę na stronach pl/firesecurityproducts.com lub kontakt z przedstawicielem handlowym.

Last updated on 12 November 2026 - 18:57