# AS270-F

## Indoor siren, 1 tone - NFa2P approved

The AS270 series of sirens is ideal for use as an internal alarm sounder for residential and industrial alarm applications.



## Details

- Low current consumption
- Pry-off & opening tamper protection
- Easy to install (1 fixing screw for cover)
- Vertical or horizontal mounting
- Self activating version available
- ANPI, NFA2P and VdS version available

# AS270-F

## Indoor siren, 1 tone - NFa2P approved

## Technical specifications

### General

| | |
|---|---|
| Accessory group | Sirene |
| Type | Indendørs sirene |
| Sounder output (dB @ distance) | 108 dB at 1 m (typical) |

### Electrical

| | |
|---|---|
| Power supply value | 10.0 to 14.2 VDC |
| Operating voltage | 10 to 14.2 V |
| Current consumption | 120 mA at 12 VDC (typical) |

### Physical

| | |
|---|---|
| Physical dimensions | 155 x 114 x 44 mm |
| Net weight | 209 g |
| Colour | Hvid |
| Material | ABS |

### Environmental

| | |
|---|---|
| Operating temperature | -25 to +55°C |
| IP rating | IP31 |

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 21 January 2026 - 19:51