9-10947

90Deg Patress Sampling Point assembly - complete

Description

The 9-10947 is a 90 degree patress sampling point. It is supplied complete with a 27mm diameter t-union, to which the flexible sample pipe connects. The flexible sampling pipe has a diameter of 10mm and is 1m long. At the end of the flexible sampling pipe, the sampling point is connected which is mounted onto the false ceiling with two screws. Due the 90 degree connection, the sampling can be installed in false ceilings where limited space is available.



9-10947

90Deg Patress Sampling Point assembly - complete

Technical specifications

Sampling pipe

Length	1 m
Diameter	10 mm (outer)
Color	Red

Physical

Physical dimensions	1 m (lenght) 65 mm (Sampling point diameter) 27 mm (Inner T-Union diameter) 10 mm (Outer capillary pipe diameter)
Colour	Hvid
Mounting type	Inserir

Environmental

Environment	Indendør

Regulatory

Certification	EN54-20

Samlping point

Diameter	65 mm
Color	White
Screw hole spacing	50 mm

T-union

Diameter	27 mm (inner)
Color	Red

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 6 December 2024 - 9:26