KMD300

Detector de Monóxido de Carbono com Base

The KMD300 detector is designed as a carbon monoxide detector for the KM300 CO detection systems. The KMD300 is an intelligent device that delivers is carbon monoxide reading to the control panel for visualization via a 3-wire bus system.



Detalhes

- Complies with UNE 23300:1984, CE, WEEE, RoHS
- Microprocessor based, SMT technology
- Electrochemical CO sensor with high gas discrimination
- Resolution of up to 1 ppm, less than 5% error in measurement
- Fast response time
- No calibration required
- Low current consumption
- BI-Colour diagnostic LED
- Supported by KM300 CO panels

KMD300

Detector de Monóxido de Carbono com Base

Especificações técnicas

Detection

Detection principle	Electrochemical
Coverage area	300 m² max.
Range	0 to 300 ppm

Physical

Physical dimensions	124 x 62 mm (Ø x H, including base)
Net weight	0.3 kg

Environmental

Operating temperature	-10°C to +40°C
Storage temperature	-10°C to +70°C
Relative humidity	10 to 95%
IP rating	42

Produtos compatíveis

Categoria	Referência	Descrição
Detection device	KZD705	Base Alto Perfil para Dispositivos KL700A e KMD300 - Kilsen
Panel	KM301	Central de Monóxido de Carbono - 1 Zona
Panel	KM302	Central de Monóxido de Carbono - 2 Zonas
Panel	KM303	Central de Monóxido de Carbono - 3 Zonas
Panel	KM304	Central de Monóxido de Carbono - 4 Zonas

Como empresa de inovação, a Kidde Global Solutions reserva o direito de alterar as especificações do produto sem aviso prévio. Para obter informações sobre as especificações mais recentes do produto, visite pt.firesecurityproducts.com online ou contate o departamento comercial.

Last updated on 12 November 2026 - 18:57